

Specifications



Photo is representative



Eaton 239588

Eaton Moeller® series DILM Contactor, 3 pole, 380 V 400 V 75 kW, RAC 240: 190 - 240 V 50/60 Hz, AC operation, Screw terminals DILM150(RAC240)

General specifications

PRODUCT NAME	Eaton Moeller® series DILM contactor
CATALOG NUMBER	239588
MODEL CODE	DILM150(RAC240)
EAN	4015082395889
PRODUCT LENGTH/DEPTH	160 mm
PRODUCT HEIGHT	170 mm
PRODUCT WIDTH	90 mm
PRODUCT WEIGHT	2.25 kg
CERTIFICATIONS	VDE 0660 CSA CE CSA File No.: 012528 CSA Class No.: 2411-03, 3211-04 UL 60947-4-1 UL IEC/EN 60947-4-1 IEC/EN 60947 UL Category Control No.: NLDX UL File No.: E29096 CSA-C22.2 No. 60947-4-1- 14
CATALOG NOTES	Contacts according to EN 50012
GLOBAL CATALOG	239588
PRODUCT TYPE	Contactor



Powering Business Worldwide

Product specifications

NUMBER OF POLES	Three-pole
10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.

Resources

CATALOGS	eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf SmartWire-DT Catalog Product Range Catalog Switching and protecting motors
CHARACTERISTIC CURVE	eaton-contactors-switch-dilm-characteristic-curve.eps eaton-contactors-switch-dilm-characteristic-curve-002.eps eaton-contactors-component-dilm-characteristic-curve-003.eps eaton-contactors-short-time-loading-dilm-characteristic-curve-002.eps
DECLARATIONS OF CONFORMITY	eaton-contactor-declaration-of-conformity-eu250750en.pdf eaton-contactor-declaration-of-conformity-uk251233en.pdf
DRAWINGS	eaton-contactors-mounting-dilm-dimensions-002.eps eaton-contactors-mounting-dilm-dimensions.eps eaton-contactors-dilm-dimensions-011.eps eaton-contactors-dilm-dimensions-003.eps eaton-contactors-dilm-3d-drawing.eps eaton-contactors-dilm-3d-drawing-013.eps eaton-general-ie-ready-dilm-contactor-standards.eps
ECAD MODEL	ETN.239588.edz

10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
FITTED WITH:	Suppressor circuit in actuating electronics
OPERATING FREQUENCY	3600 mechanical Operations/h (AC operated)
POLLUTION DEGREE	3
UTILIZATION CATEGORY	AC-1: Non-inductive or slightly inductive loads, resistance furnaces AC-3: Normal AC induction motors: starting, switch off during running AC-4: Normal AC induction motors: starting, plugging, reversing, inching
CLIMATIC PROOFING	Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
CONNECTION TO SMARTWIRE-DT	No
RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	8000 V AC
CONNECTION	Screw terminals
FRAME SIZE	FS4
AMBIENT OPERATING TEMPERATURE - MAX	60 °C
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MAX	40 °C

INSTALLATION INSTRUCTIONS	eaton-dil-contactors-instruction-leaflet-il03407039z.pdf
INSTALLATION VIDEOS	WIN-WIN with push-in technology
MCAD MODEL	DA-CS-dil_m80_170 DA-CD-dil_m80_170
PEP ECO-PASSPORT	eaton-iec-contactors-pep-eato-00125-v0101-en.pdf EATO-00022-V01.01-EN
SYSTEM OVERVIEW	eaton-contactors-dilm-contactor-system-overview.eps
WIRING DIAGRAMS	eaton-contactors-contact-dilm-wiring-diagram-003.eps

AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MIN	-25 °C
AMBIENT STORAGE TEMPERATURE - MAX	80 °C
AMBIENT STORAGE TEMPERATURE - MIN	-40 °C
ASSIGNED MOTOR POWER AT 115/120 V, 60 HZ, 1-PHASE	10 HP
ASSIGNED MOTOR POWER AT 200/208 V, 60 HZ, 3-PHASE	50 HP
ASSIGNED MOTOR POWER AT 230/240 V, 60 HZ, 1-PHASE	30 HP
ASSIGNED MOTOR POWER AT 230/240 V, 60 HZ, 3-PHASE	60 HP
ASSIGNED MOTOR POWER AT 460/480 V, 60 HZ, 3-PHASE	125 HP
CONVENTIONAL THERMAL CURRENT ITH (1-POLE, ENCLOSED)	360 A
CONVENTIONAL THERMAL CURRENT ITH (3-POLE, ENCLOSED)	144 A
CONVENTIONAL THERMAL CURRENT ITH AT 55°C (3-POLE, OPEN)	170 A
CONVENTIONAL THERMAL CURRENT ITH OF MAIN CONTACTS (1- POLE, OPEN)	400 A
EQUIPMENT HEAT DISSIPATION, CURRENT- DEPENDENT PVID	32.1 W
HEAT DISSIPATION CAPACITY PDISS	0 W
HEAT DISSIPATION PER POLE, CURRENT- DEPENDENT PVID	10.7 W
APPLICATION	Contactors for Motors
PRODUCT CATEGORY	Contactors
PROTECTION	Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN

	50274)
ARCING TIME	15 ms
ELECTRICAL CONNECTION TYPE OF MAIN CIRCUIT	Screw connection
SCREWDRIVER SIZE	2, Terminal screw, Control circuit cables, Pozidriv screwdriver 0.8 x 5.5/1 x 6 mm, Terminal screw, Control circuit cables, Standard screwdriver
VOLTAGE TYPE	AC
DEGREE OF PROTECTION	IP00
NUMBER OF AUXILIARY CONTACTS (NORMALLY CLOSED CONTACTS)	0
NUMBER OF AUXILIARY CONTACTS (NORMALLY OPEN CONTACTS)	0
NUMBER OF CONTACTS (NORMALLY CLOSED) AS MAIN CONTACT	0
NUMBER OF MAIN CONTACTS (NORMALLY OPEN CONTACT)	3
RATED BREAKING CAPACITY AT 220/230 V	1500 A
RATED BREAKING CAPACITY AT 380/400 V	1500 A
RATED BREAKING CAPACITY AT 500 V	1500 A
RATED BREAKING CAPACITY AT 660/690 V	1200 A
RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 50 HZ - MAX	240 V
RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 50 HZ - MIN	190 V
RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 60 HZ - MAX	240 V
RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 60 HZ - MIN	190 V
DROP-OUT VOLTAGE	AC operated: 0.6 - 0.25 x UC, AC operated
OVERVOLTAGE CATEGORY	III
DUTY FACTOR	100 %

EMITTED INTERFERENCE	According to EN 60947-1
INTERFERENCE IMMUNITY	According to EN 60947-1
LIFESPAN, MECHANICAL	10,000,000 Operations (AC operated)
PICK-UP VOLTAGE	0.8 - 1.15 V AC x U_c
POWER CONSUMPTION, PICK-UP, 50 Hz	180 VA, Dual-frequency coil in a cold state and $1.0 \times U_s$, at 50 Hz
SAFE ISOLATION	690 V AC, Between the contacts, According to EN 61140 690 V AC, Between coil and contacts, According to EN 61140
POWER CONSUMPTION, PICK-UP, 60 Hz	170 VA, Dual-frequency coil in a cold state and $1.0 \times U_s$, at 60 Hz
RESIDUAL CURRENT	1 mA (with actuation of A1 - A2 by the electronics with "0" signal)
SCREW SIZE	M10, Terminal screw, Main cables M3.5, Terminal screw, Control circuit cables 5 mm AF, Hexagon socket-head spanner, Terminal screw, Main cables
POWER CONSUMPTION, SEALING, 50 Hz	2.3 W, Dual-frequency coil in a cold state and $1.0 \times U_s$, at 50 Hz 3.1 VA, Dual-frequency coil in a cold state and $1.0 \times U_s$, at 50 Hz
POWER CONSUMPTION, SEALING, 60 Hz	2.3 W, Dual-frequency coil in a cold state and $1.0 \times U_s$, at 60 Hz 3.1 VA, Dual-frequency coil in a cold state and $1.0 \times U_s$, at 60 Hz
TERMINAL CAPACITY (STRANDED)	1 x (16 - 95) mm ² , Main cables 2 x (16 - 70) mm ² , Main cables
TERMINAL CAPACITY (COPPER BAND)	2 x (6 x 16 x 0.8) mm (Number of segments x width x thickness), Main cables
TERMINAL CAPACITY (FLEXIBLE WITH FERRULE)	2 x (0.75 - 2.5) mm ² , Control circuit cables 1 x (10 - 95) mm ² , Main cables 2 x (10 - 70) mm ² , Main cables

	1 x (0.75 - 2.5) mm ² , Control circuit cables
SHOCK RESISTANCE	7 g, N/O auxiliary contact, Mechanical, according to IEC/EN 60068-2-27, Half- sinusoidal shock 10 ms 5 g, N/C auxiliary contact, Mechanical, according to IEC/EN 60068-2-27, Half- sinusoidal shock 10 ms 5 g, N/C auxiliary contact, Mechanical, according to IEC/EN 60068-2-27 when tabletop-mounted, Half- sinusoidal shock 10 ms 10 g, N/O main contact, Mechanical, according to IEC/EN 60068-2-27 when tabletop-mounted, Half- sinusoidal shock 10 ms 10 g, N/O main contact, Mechanical, according to IEC/EN 60068-2-27, Half- sinusoidal shock 10 ms 7 g, N/O auxiliary contact, Mechanical, according to IEC/EN 60068-2-27 when tabletop-mounted, Half- sinusoidal shock 10 ms
TERMINAL CAPACITY (SOLID)	1 x (0.75 - 4) mm ² , Control circuit cables 2 x (0.75 - 2.5) mm ² , Control circuit cables
TERMINAL CAPACITY (SOLID/STRANDED AWG)	18 - 14, Control circuit cables Single 8...3/0, double 8...2/0, Main cables
SWITCHING CAPACITY (MAIN CONTACTS, GENERAL USE)	225 A, Maximum motor rating (UL/CSA)
TIGHTENING TORQUE	14 Nm, Screw terminals, Main cables 1.2 Nm, Screw terminals, Control circuit cables
RATED INSULATION VOLTAGE (UI)	690 V
RATED MAKING CAPACITY UP TO 690 V (COS PHI TO IEC/EN 60947)	2100 A
RATED OPERATIONAL CURRENT (IE) AT AC-1, 380 V, 400 V, 415 V	190 A
RATED OPERATIONAL CURRENT (IE) AT AC-3, 220 V, 230 V, 240 V	150 A

RATED OPERATIONAL	
CURRENT (IE) AT AC-3,	150 A
380 V, 400 V, 415 V	
RATED OPERATIONAL	
CURRENT (IE) AT AC-3,	150 A
440 V	
RATED OPERATIONAL	
CURRENT (IE) AT AC-3,	150 A
500 V	
RATED OPERATIONAL	
CURRENT (IE) AT AC-3,	100 A
660 V, 690 V	
RATED OPERATIONAL	
CURRENT (IE) AT AC-4,	65 A
220 V, 230 V, 240 V	
RATED OPERATIONAL	
CURRENT (IE) AT AC-4,	65 A
400 V	
RATED OPERATIONAL	
CURRENT (IE) AT AC-4,	65 A
440 V	
RATED OPERATIONAL	
CURRENT (IE) AT AC-4,	65 A
500 V	
RATED OPERATIONAL	
CURRENT (IE) AT AC-4,	50 A
660 V, 690 V	
RATED OPERATIONAL	
CURRENT (IE) AT DC-1,	160 A
110 V	
RATED OPERATIONAL	
CURRENT (IE) AT DC-1,	90 A
220 V	
RATED OPERATIONAL	
CURRENT (IE) AT DC-1, 60	160 A
V	
RATED OPERATIONAL	
CURRENT FOR SPECIFIED	150 A
HEAT DISSIPATION (IN)	
RATED OPERATIONAL	
POWER AT AC-3, 240 V, 50	52 kW
Hz	
RATED OPERATIONAL	
POWER AT AC-3, 380/400	75 kW
V, 50 Hz	
RATED OPERATIONAL	
POWER AT AC-3, 415 V, 50	91 kW
Hz	
RATED OPERATIONAL	
POWER AT AC-4, 220/230	20 kW
V, 50 Hz	
RATED OPERATIONAL	
POWER AT AC-4, 240 V, 50	22 kW

Hz**RATED OPERATIONAL**

POWER AT AC-4, 380/400 V, 50 Hz 33 kW

RATED OPERATIONAL

POWER AT AC-4, 415 V, 50 Hz 39 kW

RATED OPERATIONAL

POWER AT AC-4, 440 V, 50 Hz 41 kW

RATED OPERATIONAL

POWER AT AC-4, 500 V, 50 Hz 47 kW

RATED OPERATIONAL

POWER AT AC-4, 660/690 V, 50 Hz 48 kW

RATED OPERATIONAL

POWER (NEMA) 93 kW

RESISTANCE PER POLE

0.6 mΩ

STATIC HEAT

DISSIPATION, NON-CURRENT-DEPENDENT PVS 2.3 W

STRIPPING LENGTH

(CONTROL CIRCUIT CABLE) 10 mm

STRIPPING LENGTH

(MAIN CABLE) 24 mm

SWITCHING TIME (AC

OPERATED, MAKE CONTACTS, CLOSING DELAY) - MAX 33 ms

SWITCHING TIME (AC

OPERATED, MAKE CONTACTS, CLOSING DELAY) - MIN 28 ms

SWITCHING TIME (AC

OPERATED, MAKE CONTACTS, OPENING DELAY) - MAX 41 ms

SWITCHING TIME (AC

OPERATED, MAKE CONTACTS, OPENING DELAY) - MIN 35 ms

SHORT-CIRCUIT CURRENT RATING (BASIC RATING) 10 kA, 600 A max. fuse,
SCCR (UL/CSA)
10 kA, 600 A max. CB,
SCCR (UL/CSA)

SHORT-CIRCUIT CURRENT RATING (HIGH FAULT AT 100 kA, 600 A CLASS J max.
fuse, SCCR (UL/CSA)

480 V)

SHORT-CIRCUIT CURRENT RATING (HIGH FAULT AT 600 V) 100 kA, 600 A CLASS J max. fuse, SCCR (UL/CSA)

SHORT-CIRCUIT PROTECTION RATING (TYPE 1 COORDINATION) AT 400 V 250 A gG/gL

SUITABLE FOR Also motors with efficiency class IE3

SHORT-CIRCUIT PROTECTION RATING (TYPE 1 COORDINATION) AT 690 V 250 A gG/gL

SHORT-CIRCUIT PROTECTION RATING (TYPE 2 COORDINATION) AT 400 V 250 A gG/gL

SHORT-CIRCUIT PROTECTION RATING (TYPE 2 COORDINATION) AT 690 V 250 A gG/gL

SPECIAL PURPOSE RATING OF BALLAST ELECTRICAL DISCHARGE LAMPS 160 A (600V 60Hz 3phase, 347V 60Hz 1phase)
160 A (480V 60Hz 3phase, 277V 60Hz 1phase)

SPECIAL PURPOSE RATING OF DEFINITE PURPOSE RATING 150 A, FLA 480 V 60 Hz 3-ph, 100,000 cycles acc. to UL 1995, (UL/CSA)
900 A, LRA 480 V 60 Hz 3-ph, 100,000 cycles acc. to UL 1995, (UL/CSA)

SPECIAL PURPOSE RATING OF ELEVATOR CONTROL 75 HP, 480 V 60 Hz 3-ph, (UL/CSA)
99 A, 600 V 60 Hz 3-ph, (UL/CSA)
104 A, 240 V 60 Hz 3-ph, (UL/CSA)
40 HP, 240 V 60 Hz 3-ph, (UL/CSA)
30 HP, 200 V 60 Hz 3-ph, (UL/CSA)
96 A, 480 V 60 Hz 3-ph, (UL/CSA)
100 HP, 600 V 60 Hz 3-ph, (UL/CSA)
92 A, 200 V 60 Hz 3-ph, (UL/CSA)

SPECIAL PURPOSE RATING OF REFRIGERATION CONTROL (CSA ONLY) 540 A, LRA 600 V 60 Hz 3phase; (CSA)
540 A, LRA 480 V 60 Hz 3phase; (CSA)
90 A, FLA 600 V 60 Hz 3phase; (CSA)
90 A, FLA 480 V 60 Hz 3phase; (CSA)

SPECIAL PURPOSE RATING OF RESISTANCE AIR HEATING	160 A, 480 V 60 Hz 3phase, 277 V 60 Hz 1phase, (UL/CSA) 160 A, 600 V 60 Hz 3phase, 347 V 60 Hz 1phase, (UL/CSA)
SPECIAL PURPOSE RATING OF TUNGSTEN INCANDESCENT LAMPS	160 A, 600 V 60 Hz 3phase, 347 V 60 Hz 1phase, (UL/CSA) 160 A, 480 V 60 Hz 3phase, 277 V 60 Hz 1phase, (UL/CSA)
CONVENTIONAL THERMAL CURRENT ITH AT 40°C (3-POLE, OPEN)	190 A
CONVENTIONAL THERMAL CURRENT ITH AT 50°C (3-POLE, OPEN)	180 A
CONVENTIONAL THERMAL CURRENT ITH AT 60°C (3-POLE, OPEN)	160 A
RATED OPERATIONAL POWER AT AC-3, 440 V, 50 HZ	95 kW
RATED OPERATIONAL POWER AT AC-3, 500 V, 50 HZ	110 kW
RATED OPERATIONAL POWER AT AC-3, 690 V, 50 HZ	96 kW
ACTUATING VOLTAGE	RAC 240: 190 - 240 V 50/60 Hz
ALTITUDE	Max. 2000 m
OPERATING VOLTAGE AT AC, 50 HZ - MIN	230 V
OPERATING VOLTAGE AT AC, 50 HZ - MAX	690 V
OPERATING VOLTAGE AT AC, 60 HZ - MIN	230 V
OPERATING VOLTAGE AT AC, 60 HZ - MAX	690 V

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

